

FULL FORCE STRIPPER

TECHNICAL DATA SHEET

CLASSIFICATION: FLOOR FINISH & SEAL STRIPPER

PACKAGING: 4L (1 gal) Jug | 20L (5.2 gal) Pail

DESCRIPTION:

- ⇒ **Full Force** is a non-ammoniated, extremely concentrated stripper which removes chemical resistant coatings, including sealers and urethane containing coatings.
- ⇒ **Full Force** may be used on a wide variety of resilient and non-resilient flooring including vinyl, vinyl composite tile, ceramic tile, and concrete.
- ⇒ **Full Force** should not be used on wood, cork, linoleum or rubber floors.
- ⇒ **Full Force** may be used with autoscrubbers or conventional floor care equipment.

CHEMICAL AND PHYSICAL PROPERTIES

APPEARANCE:	Clear Fluorescent Yellow Liquid	ODOUR:	Solvent
pH, CONCENTRATE:	12 - 13	pH, 1:18:	11
SPECIFIC GRAVITY:	1.03	VISCOSITY:	20 – 40 cps

USE INSTRUCTIONS:

- Dilution: Prepare use solutions of **Full Force** in cold water.

Build-Up	Dilution	mL/L	Coverage* sq feet
Light	1:24	42	2,000
Medium	1:18	53	1,500
Heavy	1:12	77	1,000

* Per litre of concentrate

- Apply stripping solution liberally to floor with mop.
- Allow to work for 5-10 minutes; more contact time may be required for sealer removal. Do not allow the floor to dry. Rewet with stripping solution as required.
- Scrub with low speed (175-350 rpm) floor machine (or autoscrubber) equipped with a black or high productivity stripping pad or stripping brush.
- Pick up solution with an autoscrubber or wet vac.
- Rinse well with clean water and allow the floor to thoroughly dry.
- Apply floor coatings according to label directions, as needed.

See Material Safety Data Sheet for Proper Handling and Safety Instructions.